

Opel Kadett



OPEL KADETT 1,3 GL AND GLS 5 DOOR

SPECIFICATIONS

DIMENSIONS

Length (mm).....	3998
Width (mm).....	1637
Height (mm).....	1325
Wheelbase (mm).....	2514
Tread Front/Rear (mm).....	1400/1406
Shoulder Room Front/Rear (mm).....	1340/1345
Head Room Front/Rear (mm).....	968/937
Max. Leg Room Front/Rear (mm).....	1061/892
Overhang Front/Rear (mm).....	741/743
Ground Clearance (mm).....	128
Trunk Capacity (dm ³) seats up/down.....	270/821
Fuel Tank Capacity (litres).....	55
Wheel Type.....	Styled
Size.....	5J x 13
Tyre Size.....	155 SR 13
Turning Circle, lock to lock (m).....	3,9
Turning Circle, wall to wall (m).....	10,7

POWERPLANT

Engine Type.....	IL-OHC
Number of Cylinders.....	4
Displacement (cm ³).....	1297 (1,3)
Net Output kW at r/min.....	55 @ 5800
Net Torque Nm at r/min.....	101 @ 3800/4600
Compression Ratio.....	9,2:1
Bore (mm).....	75,0
Stroke (mm).....	73,4
Number of Main Bearings.....	5
Carburettor.....	Varajet II
Alternator.....	D/D 2BBL 12V 40 Amp

TRANSMISSION RATIOS

4 speed synchromesh transmission	Manual
1st.....	3,636:1
2nd.....	2,188:1
3rd.....	1,429:1
4th.....	0,969:1
Reverse.....	3,182:1
Axle Ratio.....	4,18 :1

FEATURES

Luxury (Appearance Features)

Metallic paint (optional)
Chrome exhaust extension

Comfort and Convenience

Engine compartment light
Trunk compartment light
Glove compartment light
Two speed heater/demister
Thru-flow ventilation
Side window demisters
Front door operated courtesy light
Day/night interior rear view mirror
Courtesy mirror in passenger sunvisor
Carpeted boot
Fully reclining front bucket seats

Front and rear door armrests
Rear passenger assist straps
Rear coat hooks
Cigar lighter
Cigar lighter light
Ashtrays front and rear
Front ashtray light
Centre floor console
2-spoke soft-feel steering wheel
Security cover

Engineering and Safety

Laminated windshield
Energy absorbing steering column
Steering wheel lock
Childproof rear door locks
Recessed exterior door handles
Headlamp flasher
Emergency flasher
Radial ply tyres
McPherson strut front suspension
Coil spring rear suspension
Power assisted brakes
Front disc brakes
Rear drum brakes
Dual Master Cylinder braking system
Two speed wiper plus intermittent wipe
Twin windscreen washers
Rear window wiper and washer
Single Halogen headlamps
Reverse lights
Safety breakaway rear view mirror
Locking petrol cap
Rubberised undercoating
3-point Lap/Diagonal inertia reel seat belts
Nylon insert body side protection mouldings
Impact resistant bumpers
Safety padded instrument panel

Instrumentation

Anti-glare instrumentation
Instrumentation compartment panel light
Electric clock
Temperature gauge
Brake fluid level warning light
Parking brake warning light

Additional Standard Features GL

Loop pile floor carpeting
Vinyl trim seats
Three quarter door trim
Centre wheel caps

GLS

Cut pile floor carpeting
Full cloth trim seats with head restraints
Full door trim
Side coach stripe
Chrome trim rings with centre wheel cap

OPEL KADETT 1,3 GL EN GLS 5-DEUR

SPESIFIKASIES

AFMETINGS

Langte (mm).....	3998
Breedte (mm).....	1637
Hoogte (mm).....	1325
Asafstand (mm).....	2514
Spoorbreedte Voor/Agter (mm).....	1400/1406
Skouerruimte Voor/Agter (mm).....	1340/1345
Kopruimte Voor/Agter (mm).....	968/937
Maks. Beenruimte Voor/Agter (mm).....	1061/892
Oorhang Voor/Agter (mm).....	741/743
Grondvryhoogte (mm).....	128
Bagasieruimte (dm ³) Sitplekke op/af.....	270/821
Brandstofteenk-inhoud (liter).....	55
Wieltype.....	Gestileer
grootte.....	5J x 13
Bandgrootte.....	155 SR 13
Draaisirkel, kant tot kant (m).....	3,9
Draaisirkel, muur tot muur (m).....	10,7

KRAGBRON

Enjintipe.....	IL-Bonokas
Getal silinders.....	4
Verplasing (cm ³).....	1297 (1,3)
Netto drywing kW teen r/min.....	55 @ 5800
Netto wringkrag Nm teen r/min.....	101 @ 3800/4600
Drukverhouding.....	9,2:1
Boring (mm).....	75,0
Slag (mm).....	73,4
Getal hooflaers.....	5
Vergasser.....	Varajet II
Alternator.....	V/S 2BBL 12V 40 Amp

RATVERHOUDINGS

Gesinchroniseerde 4-gang-ratkas	Handrat
1e.....	3,636:1
2e.....	2,188:1
3e.....	1,429:1
4e.....	0,969:1
Trurat.....	3,182:1
Asverhouding.....	4,18 :1

KENMERKE

Weelde (Voorkomskenmerke)

Metaalglansverf (opsioneel)
Chroom-uitlaatverlenging

Gemak en Gerief

Lig in enjinruim
Lig in bagasieruim
Lig in paneelkassie
Tweespoed-verwarmer/ontwasemer
Deurvloeventilasie
Syvenster-ontwasemer
Voordeur-beheerde hoflikheidslig
Dag/nagbinnetruspieël
Smukspieël in passasiersonkerm
Bagasieruim met tapyt
Volterugleun-holrugsitplekke voor
Voor- en agterdeurarmleunings
Vashoustrappe vir agterpassasiers

Klerehake agter
Sigaretaanstecker
Sigaretaansteckerlig
Asbakkes voor en agter
Lig vir voorste asbakke
Middelvloerkonsole
Sagvoel-2-speek-stuurwiel
Veiligheidsdeksel

Ingenieurswerk en Veiligheid

Gelamelleerde voorruit
Skokbrekende stuurkolom
Stuurwielslot
Kinderveilige agterdeurslotte
Ingelate buitedeurhandvatsels
Koplampflitser
Noodflikkers
Straalbande
McPherson-stut-veerstelsel voor
Kronkelveerstelsel agter
Krag-gesteunde remme
Skytremme voor
Trommelremme agter
Dubbelhoofsilinder-remstelsel
Tweespoedveer met afwissel-aksie
Twee voorruitspuite
Agterruitveer met ruitspuit
Parkeerrem-waarskulig
Enkel-halooenkoplampe
Truligte
Knaktipe veiligheidsruspieël
Sluitbare petroltenkdeur
Gerubberiseerde onderlaag
Skoot/oorkruistipe 3-punt-rukstopgordels
Beskermdende nylon-inlegsel-bakstrokke
Stampwerende buffers
Veiligheid-opgestopte instrumentpaneel

Instrumentasie

Skyinselwerende instrumentasie
Instrumentpaneellig
Elektriese horlosie
Temperatuurmeter
Remvloeistofpeil-waarskulig
Parkeerrem-waarskulig

Bykomende standaardkenmerke GL

Luspoolvloertapyt
Vinieelplekbekleedsel
¾ Deurbeslag
Middelwieldoppe

GLS

Pluispoolvloertapyt
Sitplekke met volle weefstofbekleedsel en kopstutte
Volle deurbeslag
Sysierstreep
Chroomsierringe met middelwieldop

General Motors warranty has been extended to 12 months or 20 000 km, with service intervals of 6 months or 10 000 km.
General Motors South African (Pty) Limited reserves the right to make changes at any time in prices, materials, equipment, specifications and models and also to discontinue models.
This right may be exercised without incurring any responsibility with regard to vehicles previously sold.



General Motors se waarborg is tot 12 maande of 20 000 km verleng, met versiening elke 6 maande of 10 000 km.
General Motors Suid-Afrika (Edms) Beperk behou hulle die reg voor om enige tyd veranderinge in pryse, materiaal, toerusting, spesifikasies en modelle aan te bring en ook modelle te staak.
Hierdie reg kan uitgeoefen word sonder enige aanspreeklikheid met betrekking tot voertuie vantevore verkoop.